

Kód zboží	Výška (mm)	Šířka (mm)	Připojovací rozteč (mm)	t1/t2 (°C)	Q[W] tj (20 °C)	Vodní objem (l)	Doporučený výkon pro elektrické vytápění (W)
KH450730S	730	450	420	9070	400	3,3	300
KH600730S	730	600	570	9070	520	4,1	300
KH750730S	730	750	720	9070	637	5	400
KH450970S	970	450	420	9070	520	4,2	300
KH600970S	970	600	570	9070	676	5,3	400
KH750970S	970	750	720	9070	828	6,4	600
KH4501320S	1330	450	420	9070	705	5,7	500
KH6001320S	1330	600	570	9070	917	7,2	600
KH7501320S	1330	750	720	9070	1124	8,7	800
KH4501690S	1690	450	420	9070	901	7,2	600
KH6001690S	1690	600	570	9070	1172	9,1	800
KH7501690S	1690	750	720	9070	1436	10,9	1000
KH4501850S	1850	450	420	9070	992	8,5	600
KH6001850S	1850	600	570	9070	1290	10,5	800
KH7501850S	1850	750	720	9070	1581	12,6	1000
KH450970SBL	970	450	420	9070	520	4,2	300
KH6001320SBL	1330	600	570	9070	917	7,2	600

Způsoby připojení

